

# Isolator TYPE DNK

DIN-Rail IEC/EN60947-3 Isolator Switch (240V/415V)

1

Miniature Circuit Breakers

## Structure Characteristics

Two-function connected wire terminal with indicator for contact status can hand lock, Voltage 240/415V, Frequency 50/60Hz.

## Applications

Its used for industry, Commercial and residence circuit electrical wire, used as mainly switch IEC/EN60947-3

## Marking

CE



| Rating | Ref.No. | 1Pole   | Ref.No. | 2Poles  | Ref.No. | 3Poles  | Ref. No. | 4Poles  |
|--------|---------|---------|---------|---------|---------|---------|----------|---------|
| 16     | W601026 | DNK116  | W601034 | DNK216  | -       | -       | -        | -       |
| 25     | W601027 | DNK125  | W601035 | DNK225  | -       | -       | -        | -       |
| 32     | W601028 | DNK132  | W601036 | DNK232  | W601042 | DNK332  | W601048  | DNK432  |
| 40     | W601029 | DNK140  | W601037 | DNK240  | W601043 | DNK340  | W601049  | DNK440  |
| 63     | W601030 | DNK163  | W601038 | DNK263  | W601044 | DNK363  | W601050  | DNK463  |
| 80     | W601031 | DNK180  | W601039 | DNK280  | W601045 | DNK380  | W601051  | DNK480  |
| 100    | W601032 | DNK1100 | W601040 | DNK2100 | W601046 | DNK3100 | W601052  | DNK4100 |
| 125    | W601033 | DNK1125 | W601041 | DNK2125 | W601047 | DNK3125 | W601053  | DNK4125 |

## Dimensions

