

MCB Type DQ

Cable in / Cable out IEC/EN 60898-1 Circuit Breakers 10kA & 6kA (240V/415V)

Feature


DQ-MCBs are available with a breaking capacity of 10kA or 6kA Curve "C&B" to IEC/EN 60898-1, The MCB are calibrated to 40°C MCBs can be supplied with 50°C ambient calibration. Voltage 240/415V, Frequency 50/60Hz.

To order insert at the end of MCB list number DQ1C06H ref. W600288.

Description

Protection and control of circuits against overloads & short circuits for domestic and industrial installations.

Marking



DQ Cable in / Cable out IEC/EN 60898-1 Circuit Breakers. 10kA Curve C

Rating	Ref.No.	1 Pole	Ref.No.	2 Pole	Ref.No.	3 Poles	Ref.No.	4 Poles
6	W600288	DQ1C06H	W600297	DQ2C06H	W600306	DQ3C06H	W600315	DQ4C06H
10	W600289	DQ1C10H	W600298	DQ2C10H	W600307	DQ3C10H	W600316	DQ4C10H
16	W600290	DQ1C16H	W600299	DQ2C16H	W600308	DQ3C16H	W600317	DQ4C16H
20	W600291	DQ1C20H	W600300	DQ2C20H	W600309	DQ3C20H	W600318	DQ4C20H
25	W600292	DQ1C25H	W600301	DQ2C25H	W600310	DQ3C25H	W600319	DQ4C25H
32	W600293	DQ1C32H	W600302	DQ2C32H	W600311	DQ3C32H	W600320	DQ4C32H
40	W600294	DQ1C40H	W600303	DQ2C40H	W600312	DQ3C40H	W600321	DQ4C40H
50	W600295	DQ1C50H	W600304	DQ2C50H	W600313	DQ3C50H	W600322	DQ4C50H
63	W600296	DQ1C63H	W600305	DQ2C63H	W600314	DQ3C63H	W600323	DQ4C63H

① Option Curve "D" Available

MCB Type DQ

Cable in / Cable out IEC/EN 60898-1 Circuit Breakers 10kA & 6kA (240V/415V)

DQ Cable in / Cable out IEC/EN 60898-1 Circuit breaker. 6kA Curve C

Rating	Ref.No.	1 Pole	Ref.No.	2 Pole	Ref.No.	3 Poles	Ref.No.	4 Poles
6	W600324	DQ1C06S	W600333	DQ2C06S	W600342	DQ3C06S	W600351	DQ4C06S
10	W600325	DQ1C10S	W600334	DQ2C10S	W600343	DQ3C10S	W600352	DQ4C10S
16	W600326	DQ1C16S	W600335	DQ2C16S	W600344	DQ3C16S	W600353	DQ4C16S
20	W600327	DQ1C20S	W600336	DQ2C20S	W600345	DQ3C20S	W600354	DQ4C20S
25	W600328	DQ1C25S	W600337	DQ2C25S	W600346	DQ3C25S	W600355	DQ4C25S
32	W600329	DQ1C32S	W600338	DQ2C32S	W600347	DQ3C32S	W600356	DQ4C32S
40	W600330	DQ1C40S	W600339	DQ2C40S	W600348	DQ3C40S	W600357	DQ4C40S
50	W600331	DQ1C50S	W600340	DQ2C50S	W600349	DQ3C50S	W600358	DQ4C50S
63	W600332	DQ1C63S	W600341	DQ2C63S	W600350	DQ3C63S	W600359	DQ4C63S

DQ Cable in / Cable out IEC/EN 60898-1 Circuit breaker. 10kA Curve B

Rating	Ref.No.	1 Pole	Ref.No.	2 Pole	Ref.No.	3 Poles	Ref.No.	4 Poles
6	W600423	DQ1B06H	W600369	DQ2B06H	W600378	DQ3B06H	W600387	DQ4B06H
10	W600424	DQ1B10H	W600370	DQ2B10H	W600379	DQ3B10H	W600388	DQ4B10H
16	W600425	DQ1B16H	W600371	DQ2B16H	W600380	DQ3B16H	W600389	DQ4B16H
20	W600426	DQ1B20H	W600372	DQ2B20H	W600381	DQ3B20H	W600390	DQ4B20H
25	W600427	DQ1B25H	W600373	DQ2B25H	W600382	DQ3B25H	W600391	DQ4B25H
32	W600428	DQ1B32H	W600374	DQ2B32H	W600383	DQ3B32H	W600392	DQ4B32H
40	W600429	DQ1B40H	W600375	DQ2B40H	W600384	DQ3B40H	W600393	DQ4B40H
50	W600430	DQ1B50H	W600376	DQ2B50H	W600385	DQ3B50H	W600394	DQ4B50H
63	W600431	DQ1B63H	W600377	DQ2B63H	W600386	DQ3B63H	W600395	DQ4B63H

DQ Cable in / Cable out IEC/EN 60898-1 Circuit breaker. 6kA Curve B

Rating	Ref.No.	1 Pole	Ref.No.	2 Pole	Ref.No.	3 Poles	Ref.No.	4 Poles
6	W600396	DQ1B06S	W600405	DQ2B06S	W600414	DQ3B06S	W600423	DQ4B06S
10	W600397	DQ1B10S	W600406	DQ2B10S	W600415	DQ3B10S	W600424	DQ4B10S
16	W600398	DQ1B16S	W600407	DQ2B16S	W600416	DQ3B16S	W600425	DQ4B16S
20	W600399	DQ1B20S	W600408	DQ2B20S	W600417	DQ3B20S	W600426	DQ4B20S
25	W600400	DQ1B25S	W600409	DQ2B25S	W600418	DQ3B25S	W600427	DQ4B25S
32	W600401	DQ1B32S	W600410	DQ2B32S	W600419	DQ3B32S	W600428	DQ4B32S
40	W600402	DQ1B40S	W600411	DQ2B40S	W600420	DQ3B40S	W600429	DQ4B40S
50	W600403	DQ1B50S	W600412	DQ2B50S	W600421	DQ3B50S	W600430	DQ4B50S
63	W600404	DQ1B63S	W600413	DQ2B63S	W600422	DQ3B63S	W600431	DQ4B63S

① Option Curve "D" Available

1

Miniature Circuit Breakers

MCB Type DQ

Cable in / Cable out IEC/EN 60898-1 Circuit Breakers 10kA & 6kA (240V/415V)

Dimensions

