

# Electromagnetic Relay

**WHHC68BVL - 2Z**  
**(WHH52P, MY2)**


Ref.No. W605119

Electromagnetic Relay

Output contact	2H, 2D, 2Z
Rated load	6.5A 240VAC/28VDC
Coil power	DC: 0.9W AC: 1.2VA
Coil voltage	DC:3V-220V AC:3V-380V
Dimension	27.3 x 21 x 36.2mm

**WHHC68BVL- 4Z**  
**(WHH54P, MY4)**


Ref.No. W605120

Electromagnetic Relay

Output contact	4H, 4D, 4Z
Rated load	5A/240VAC28VDC
Coil power	DC: 0.9W AC: 1.2VA
Coil voltage	DC: 6V-220V AC: 6V-380V
Dimension	27.3 x 21 x 36.2mm

**WHHC68B - 4Z**  
**(WHH54P, MY4)**


Ref.No. W605121

Electromagnetic Relay

Dimension(mm)	27.3 x 21 x 35
Contact form	4A,4B,4C
Rated load	3A 240VAC/28VDC
Contact Material	Silver alloy
Electric life	$\geq 10^5$ time
Pick-up voltage(23°C)	DC $\leq 75\%$ x Rated voltage AC $\leq 80\%$ x Rated voltage
Release voltage(23°C)	DC $\geq 10\%$ x Rated voltage AC $\geq 30\%$ x Rated voltage
Coil voltage	DC DC3V-220V AC AC3V-380V
Coil power	DC:0.9W AC:1.2VA
Operate/Release time	$\leq 15$ ms / $\leq 10$ ms

**WHHC68BVL -2Z 10A**  
**(WHH52P, MY2)**


Ref.No. W605122

Electromagnetic Relay

Output contact	2H, 2D, 2Z
Rated load	10A/240VAC 28VDC
Coil power	DC: 0.9W AC: 1.2VA
Coil voltage	DC:3V- 220V AC:3V- 380V
Dimension	27.3 x 21 x 36.2mm

**WHHC68BZL-4Z**  
**(WHH54P, MY4)**


Ref.No. W605123

Electromagnetic Relay

Output contact	4H, 4D, 4Z
Rated load	5A240VAC/28VDC
Coil power	DC: 0.9W AC: 1,2VA
Coil voltage	DC: 6V-220V AC: 6V-380V
Dimension	27.3 x 21 x 36.2mm

# Relay Socket

**WPYF14A1**  
**WPYE14A - E**



Ref.No. W605125

Relay Socket

Dimension (mm)	75.5 x 29 x 30
Rated load	7A
Rated voltage	300V
Dielectric strength	2500VAC/S
Application	WHHC68B 4Z WHHC68BZ 4Z WJQX18F-4Z WHH54P WMY4

**WPYF14A-E2**  
**WPYF08A-E2**



Ref.No. W605126

Relay Socket

Dimension (mm)	
Rated load	WPYF14A-E2:10A WPYF08A-E2:12A
Rated voltage	300V
Dielectric strength	2500VAC/S
Application	WHHC68B-2Z/4Z WHHC68BZ-2Z/4Z WJQX-18F-2Z/4Z WHHC68B-2Z/4Z WHH52P/HH54P WMY2/MY4

**WPYE14A**



Ref.No. W605127

Relay Socket

Dimension(mm)	65 x 30x 25.5
Rated load	7A
Rated voltage	300V
Dielectric strength	2500VAC/S
Application	WHHC68B 4Z WHHC68BZ 4Z WJQX 18F 4Z WHH54P WMY4